

Interiorluminaire for ceiling or suspended mounting. Suitable for use in schools.

Sheetmetal housing with RAL 9010 textured white paint. Endcaps of frosted acrylic glass. Doubleparabolic louvre with opal diffuser (SP).

### Suspended fixture:

Opening on upper side of fixture for some light on the ceiling. Supplied with adjustable suspension wire and 2.5 m cable and plug.

### Ceiling fitting:



With or without end inserts.

Dimmable version (TDC) equipped with Dali dimmable driver, push-button control and corridor function. Suspended version equipped with 5-wire connection cable.

Can be fitted with sensor and pull-switch.

Lifespan L80 Ta25 70000h (B50)  
MacAdam 3 SDCM CRI: >80

IP 20 | CE



Accessory	Art no.	E-no.
Suspension wire for ceiling fixture	9 551 83	70 152 93
Rails for 600 T-section with slide screws	9 552 18	70 143 72
M6 clips for T-section	9 552 08	-

### Suspended

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 5000	5090	1 592 14-U	70 108 26	5300	1 592 30-U	70 137 64	1260	152	50	1200	40	3
ClassLED 5000 TDC *	5090	1 592 15-U	70 108 28	5300	1 592 17-U	70 137 63	1260	152	50	1200	40	3
ClassLED 6000	6180	1 592 60-U	70 137 61	6440	1 592 62-U	70 137 62	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	6180	1 592 64-U	70 137 34	6440	1 592 66-U	70 137 35	1560	152	50	1310	50	3,5

### Ceiling

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 2000	2090	1 592 10	70 118 28	2180	1 592 24	70 137 53	660	152	50	600	20	2
ClassLED 2000 TDC *	2090	1 592 12	70 118 29	2180	1 592 25	70 137 54	660	152	50	600	20	2
ClassLED 5000	4810	1 592 14	70 108 25	4950	1 592 13	70 137 51	1260	152	50	1200	40	3
ClassLED 5000 TDC *	4810	1 592 15	70 108 27	4950	1 592 21	70 137 52	1260	152	50	1200	40	3
ClassLED 6000	5840	1 592 60	70 137 59	6090	1 592 62	70 137 60	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	5840	1 592 64	70 137 81	6090	1 592 66	70 137 82	1560	152	50	1310	50	3,5

### Ceiling with end connection

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 2000	2090	1 592 11	70 137 73	2180	1 592 27	70 137 78	660	152	50	600	20	2
ClassLED 2000 TDC *	2090	1 592 23	70 137 77	2180	1 592 28	70 137 79	660	152	50	600	20	2
ClassLED 5000	4750	1 592 16	70 137 74	4950	1 592 19	70 137 76	1260	152	50	1200	40	3
ClassLED 5000 TDC *	4750	1 592 18	70 137 75	4950	1 592 29	70 137 80	1260	152	50	1200	40	3
ClassLED 6000	5840	1 592 68	70 137 83	6090	1 592 70	70 137 84	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	5840	1 592 72	70 137 85	6090	1 592 74	70 137 86	1560	152	50	1310	50	3,5

\* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.