



Luminaire for damp and dusty environments, multi-storey car parks, etc. extra resistance for chemicals.

D-marked enclosed IP 65 fixture. Housing made of glassfiberreinforced polyester. Frostad diffuser of acrylic. Stainless steel mounting clips. Detachable suspension brackets with adjustable c/c, distance +/-70 mm.

Fitted flush to ceiling, on wallbracket, rails or wires.

Connection via ends. 3-phase 5x2.5mm<sup>2</sup> throughwiring in housing, with dimming as standard Single-phase throughwiring.

Fitted with robust industrydriver with good resistance to voltagesurges.

Available in several versions depending on dimming, control and connection options.

Lifetime L80 Ta25 100000h (B50)  
MacAdam 3 SDCM CRI: >80

IP 65 D | IK 04 | CE



Detachable suspension brackets





Wire bracket



Quick connection

Accessory	Part no.	E-no.
Wire bracket (pair)	9 550 30	79 550 30
Shelterbracket	9 550 26	-
Adjustable bracket (pair)	9 550 18	79 550 19
45/90 bracket (pair)	9 550 10	79 550 10
45 bracket (pair)	9 550 11	-



Type	Lumen	Art. no. 830	E-no.	Lumen	Art. no. 840	E-no.	L	W	H	c/c	Power	Weight
ID 65 LED GRP 5000	4910	4 527 61	72 150 71	5010	4 527 65	72 150 73	1477	85	88	1000	31	4,5
ID 65 LED GRP 5000 TDC *	4910	4 527 63	72 150 72	5010	4 527 67	72 150 74	1477	85	88	1000	31	4,5
ID 65 LED GRP 8000	8220	4 527 51	72 150 75	8290	4 527 55	72 150 77	1477	85	88	1000	54	4,5
ID 65 LED GRP 8000 TDC *	8220	4 527 53	72 150 76	8290	4 527 57	72 150 78	1477	85	88	1000	54	4,5

\* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.