

Recessed systemluminaire that is designed for easy fitting in an unbroken continuous line.

Description:

Outer and inner part of extruded aluminium. White powdercoated RAL 9016 as standard.

Louvre:

Microspmatic (MP) alt. opalic (OP) diffuser lifted into the housing.

Mounting:

The luminaire is placed in the suspended ceiling's T-profile, spliced with guidepins and fitted together with an eccentric lock. Start and end luminaires are equipped with endcaps. Assembly other than in T-profile on request.

Connection:

The first luminaire is equipped with a 2m 5-wire cable and a free end. Built-in throughwiring 5x1.5mm² with quick connectors.



Control:

TDC: Amplitudedimming för Touch-dim, DALI and possibility for Corridorfunction.

Alternative models:

Alternative lightcolours for example 865, CRI 90 and tunable white (TW).

Lifespan L80 Ta25 70000h (B50)
MacAdam 3 SDCM CRI: >80 | CE



| Accessories | Art no. | E-no |
|---|----------|-----------|
| Endcap InMY 10mm | 9 555 10 | 70 193 62 |
| Endcap InMY 10-250mm | 9 555 11 | 70 193 63 |
| 2m connectingcable 5-wire with a free end | 9 555 14 | 70 193 66 |

Length 561 mm

| Type | Lumen 830 | Art no 830 | E no. | Lumen 840 | Art no 840 | E no. | L | W | H | Power | Weight |
|------------------|-----------|------------|-----------|-----------|------------|-----------|-----|----|----|-------|--------|
| InMY 1000 OP TDC | 1140 | 1 803 03 | 70 193 15 | 1180 | 1 803 11 | 70 193 45 | 561 | 95 | 70 | 9 | 2,4 |
| InMY 1000 MP TDC | 1010 | 1 803 07 | 70 193 44 | 1050 | 1 803 15 | 70 193 46 | 561 | 95 | 70 | 9 | 2,4 |

Length 842 mm

| Type | Lumen 830 | Art no 830 | E no. | Lumen 840 | Art no 840 | E no. | L | W | H | Power | Weight |
|------------------|-----------|------------|-----------|-----------|------------|-----------|-----|----|----|-------|--------|
| InMY 1500 OP TDC | 1710 | 1 803 83 | 70 193 58 | 1780 | 1 803 91 | 70 193 60 | 842 | 95 | 70 | 14 | 3 |
| InMY 1500 MP TDC | 1520 | 1 803 87 | 70 193 59 | 1580 | 1 803 95 | 70 193 61 | 842 | 95 | 70 | 14 | 3 |

Length 1122 mm

| Type | Lumen 830 | Art no 830 | E no. | Lumen 840 | Art no 840 | E no. | L | W | H | Power | Weight |
|------------------|-----------|------------|-----------|-----------|------------|-----------|------|----|----|-------|--------|
| InMY 2000 OP TDC | 2270 | 1 803 23 | 70 193 48 | 2370 | 1 803 31 | 70 193 50 | 1122 | 95 | 70 | 19 | 3,3 |
| InMY 2000 MP TDC | 2020 | 1 803 27 | 70 193 49 | 2110 | 1 803 35 | 70 193 51 | 1122 | 95 | 70 | 19 | 3,3 |

Length 2245 mm

| Type | Lumen 830 | Art no 830 | E no. | Lumen 840 | Art no 840 | E no. | L | W | H | Power | Weight |
|------------------|-----------|------------|-----------|-----------|------------|-----------|------|----|----|-------|--------|
| InMY 4000 OP TDC | 4550 | 1 803 63 | 70 193 53 | 4740 | 1 803 71 | 70 193 55 | 2245 | 95 | 70 | 38 | 6,5 |
| InMY 4000 MP TDC | 4050 | 1 803 67 | 70 193 54 | 4210 | 1 803 75 | 70 193 56 | 2245 | 95 | 70 | 38 | 6,5 |

* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.