



Rotatable and adjustable downlight for recessed mounting

Diecasted aluminium frame, as standard white RAL 9016.  
Frosted black polycarbonate anti-glare rings.

Cast aluminium cooling body.

Faceted high-gloss pure aluminium reflector.  
45 degree beam angle

Rotatable 360 degrees and 35 degree tiltable.

Mounted in suspended ceiling with spring clasps. Separate component unit as standard.

Comes as standard with Halogen-free 2.5 m cable with earthed plug  
Dimmable version (TD) also equipped with separate 2-wires for control.

Lifetime L80 Ta25 50000h (B50)  
MacAdams 3 SDCM CRI >80

IP 20 | CE




Rails for soft ceilings



Plate for soft ceilings

Accessory	Art no.	E-no.
Rails for soft ceilings	9 687 01	74 677 01
Plate for soft ceilings	9 665 45	75 011 49



Type	Lumen	Art no.	E-no.	Power	Weight
Neptun 2000 830	1980	2 818 01	74 021 67	19	1,6
Neptun 2000 840	2020	2 818 03	74 021 68	19	1,6
Neptun 4000 830	3840	2 818 05	74 021 69	42	1,6
Neptun 4000 840	3920	2 818 07	74 021 70	42	1,6
Neptun 2000 830 TD *	1980	2 818 09	74 021 71	19	1,6
Neptun 2000 840 TD *	2020	2 818 11	74 021 72	19	1,6
Neptun 4000 830 TD *	3840	2 818 13	74 021 73	42	1,6
Neptun 4000 840 TD *	3920	2 818 15	74 021 74	42	1,6

\* Equipped with Dalı dimmable driver or push-button

