

Interior luminaire for surface or pendant mounting with or without uplight.

Sheetmetal housing with RAL 9010 textured white paint. Plastic endcaps. Microprism with diffuser in eloxated aluminium frame.

Ceiling version :
Connection at ends or centre of fixture.
Fixing with keyhole.

Pendant and uplight version:
As standard with adjustable suspension wire with halogen-free cable 2.4 m with earthed plug. Version available with separated down-/uplight (ST).

Dimmable version (TDC) equipped with Dali dimmable driver, push-button control and corridor function.
Pendant version equipped with 5-wire cable.

AirC:
Sensorsystem with daylightcontrol, programmable with app. The sensor can also communicate wireless with several other sensors. Also possible to integrate wireless switches. Can be fitted with sensor and pull-cord switch.

Lifetime L80 Ta25 60000h (B50)
MacAdams 3 SDCM CRI: >80

IP 20 | CE 




Pendant with uplight




Adjustable wire suspension




| Accessory | Art no. | E-no. |
|---|----------|-----------|
| Rails for 600 T-section with slide screws | 9 552 18 | 70 143 72 |
| M6 clips for T-section | 9 552 08 | - |
| Switch AirC SwitchDim 1 pole | 9 688 20 | 79 852 54 |




Ceiling

| Type | Lumen 830 | Art no. 830 | E-no. | Lumen 840 | Art no. 840 | E-no. | L | W | H | c/c | Power | Weight |
|--|-----------|-------------|-----------|-----------|-------------|-----------|------|-----|----|------|-------|--------|
| OfficeLED 4000 MP | 3630 | 1 555 10 | 70 179 46 | 3780 | 1 555 11 | 70 179 47 | 1193 | 101 | 73 | 1140 | 37 | 3,6 |
| OfficeLED 4000 MP TDC * | 3630 | 1 555 20 | 70 179 48 | 3780 | 1 555 21 | 70 179 49 | 1193 | 101 | 73 | 1140 | 37 | 3,6 |
| OfficeLED 4000 MP AirC *  | 3630 | 1 547 72 | 70 179 50 | 3780 | 1 547 73 | 70 179 51 | 1193 | 101 | 73 | 1140 | 37 | 3,7 |

Pendant

| Type | Lumen 830 | Art no. 830 | E-no. | Lumen 840 | Art no. 840 | E-no. | L | W | H | c/c | Power | Weight |
|--|-----------|-------------|-----------|-----------|-------------|-----------|------|-----|----|------|-------|--------|
| OfficeLED P 4000 MP | 3630 | 1 555 30 | 70 179 52 | 3780 | 1 555 31 | 70 179 53 | 1193 | 101 | 73 | 1140 | 37 | 3,6 |
| OfficeLED P 4000 MP TDC * | 3630 | 1 555 40 | 70 179 54 | 3780 | 1 555 41 | 70 179 55 | 1193 | 101 | 73 | 1140 | 37 | 3,6 |
| OfficeLED P 4000 MP AirC  | 3630 | 1 547 74 | 70 179 56 | 3780 | 1 547 75 | 70 179 57 | 1193 | 101 | 73 | 1140 | 37 | 3,7 |

Pendant uplight

| Type | Lumen 830 | Art no. 830 | E-no. | Lumen 840 | Art no. 840 | E-no. | L | W | H | c/c | Power | Weight |
|--|-----------|-------------|-----------|-----------|-------------|-----------|------|-----|----|------|-------|--------|
| OfficeLED 6000 MP | 5810 | 1 555 50 | 70 179 58 | 6040 | 1 555 51 | 70 179 59 | 1193 | 101 | 73 | 1140 | 54 | 4 |
| OfficeLED 6000 MP TDC * | 5810 | 1 555 60 | 70 179 60 | 6040 | 1 555 61 | 70 179 61 | 1193 | 101 | 73 | 1140 | 54 | 4 |
| OfficeLED 6000 MP AirC *  | 5810 | 1 547 76 | 70 179 62 | 6040 | 1 547 78 | 70 179 63 | 1193 | 101 | 73 | 1140 | 54 | 4,1 |

Pendant uplight or downlight with separate switch

| Type | Lumen 830 | Art no. 830 | E-no. | Lumen 840 | Art no. 840 | E-no. | L | W | H | c/c | Power | Weight |
|---------------------------|-----------|-------------|-----------|-----------|-------------|-----------|------|-----|----|------|-------|--------|
| OfficeLED 6000 MP ST | 5810 | 1 555 70 | 70 179 64 | 6040 | 1 555 71 | 70 179 65 | 1193 | 101 | 73 | 1140 | 54 | 4 |
| OfficeLED 6000 MP ST TDC* | 5810 | 1 555 80 | 70 179 66 | 6040 | 1 555 81 | 70 179 67 | 1193 | 101 | 73 | 1140 | 54 | 4 |

* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.