



Pendant luminaire with 85% downlight and 15% decorative uplight. Large illuminated surface makes a pleasant experience.

Housing made of spun aluminium, Diffusor by opalized acrylic.

Connection to separated ceilingbox. Double entry 5-pole terminalblock.


Suspended in 3 pcs adjustable wires that also functions as connection to the luminaire for as discreet mounting as possible. Up to 1500mm suspensionlength.

With the accessory Recesskit Pi 600, you get a unique lightwelleffect.

As standard dimmable drivers.

Lifetime L80 Ta25 70000h (B50)  
MacAdams 3 SDCM CRI: >80


IP 20 I CE



Ceilingcup



Accessory	Part. nr.	E-no.
Recesskit Pi 600	9 557 30	-



Type	Lumen	Art. no.	E-no.	ø	H	Power	Weight
Pi 600 830 TDC*	2390	5 550 01	70 186 34	600	120	37	2,3
Pi 600 840 TDC*	2490	5 550 05	70 186 36	600	120	37	2,3
Pi 1080 830 TDC*	6490	5 550 11	70 186 37	1080	120	77	5,1
Pi 1080 840 TDC*	6760	5 550 15	70 186 38	1080	120	77	5,1

\* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.