



IP 65 downlight

For pendant (P) or ceiling mounting (S). Chromated and powder coated housing. RAL 7016 dark grey as standard.

Tempered safety glass and stainless screws. Pure aluminium reflectors.




Connected via quick-connect terminal block inside luminaire or ceiling cup for pendant version.

Can be fitted with Dali dimming.

Lifespan L80 Ta25 50000h B50
MacAdams 3 SDCM CRI: >80

IP 65 | IK 07 | CE

| Type | Lumen | Art no. | E no. | Power | Weight |
|-------------------|-------|----------|-----------|-------|--------|
| Timbal S 2000 830 | 1840 | 7 215 11 | 77 032 06 | 22 | 4,1 |
| Timbal S 2000 840 | 1880 | 7 215 13 | 77 032 07 | 22 | 4,1 |
| Timbal S 3000 830 | 2650 | 7 215 15 | 77 032 08 | 33 | 4,1 |
| Timbal S 3000 840 | 2700 | 7 215 17 | 77 032 09 | 33 | 4,1 |



| Type | Lumen | Art no. | E no. | Power | Weight |
|-------------------|-------|----------|-----------|-------|--------|
| Timbal P 2000 830 | 1840 | 7 215 19 | 77 032 10 | 22 | 4,6 |
| Timbal P 2000 840 | 1880 | 7 215 21 | 77 032 11 | 22 | 4,6 |
| Timbal P 3000 830 | 2650 | 7 215 23 | 77 032 12 | 33 | 4,6 |
| Timbal P 3000 840 | 2700 | 7 215 25 | 77 032 13 | 33 | 4,6 |