



Wall and ceiling plafoniere.

White frame and opal polycarbonate diffuser. Stainless screws for fixing the diffuser. High-impact fixture that meets IK +10 (20 J) requirements.



Also available with sensor and with 60 min emergency lighting operation.






Sensor turns on and off with motion.

Sensor corridor provides a 10% light level and increases up to 100% when presence is detected.

Lifespan L80 Ta25 50000h (B50)
MacAdam 3 SDCM CRI: >80

IP 54 | IK 10 | CE



Type	Lumen	Art no.	E no.	H	Ø	Power	Weight
Alien Maxi LED 1000 830	1190	1 516 20	75 342 35	100	335	12	1,4
Alien Maxi LED 1000 840	1230	1 516 21	-	100	335	12	1,6
Alien Maxi LED 1000 830 Sensor	 1190	1 516 22	75 342 36	100	335	12	1,4
Alien Maxi LED 1000 840 Sensor	 1230	1 516 23	-	100	335	12	1,6
Alien Maxi LED 1000 830 Sensor Korridor	 1190	1 516 24	75 342 37	100	335	12	1,4
Alien Maxi LED 1000 840 Sensor Korridor	 1230	1 516 25	-	100	335	12	1,4
Alien Maxi LED 1000 830 Korridor	1190	1 516 26	75 342 61	100	335	12	1,4
Alien Maxi LED 1000 830 Nöd	1190	1 516 20-Nöd	75 342 63	100	335	12	1,6
Alien Maxi LED 1000 830 Nöd Sensor	 1190	1 516 22-Nöd	75 342 64	100	335	12	1,6