



Wall or ceiling plafoniere.

White housing and opal polycarbonate diffuser. Stainless screws for fixing the diffuser. High-impact luminaire that meets IK 10 requirements.

Available with sensor or dimmable versions and also with 60 min emergency lighting operation.

Eco for SwitchDim, Dali or DSI dimming and Corridor function.



Sensor turns on and off with motion.











Sensor Eco lights with 10% lightlevel, increases to 100% when presence is detected.

ECO Dalisensor has several possible settings depending on requirements.

Lifespan L80 Ta25 50000h (B50)
MacAdam 3 SDCM CRI: >80

IP 54 | IK 10 | CE



Type	Lumen	Art no.	E no.	H	ø	Power	Weight
Alien XL LED 2000 830	2180	1 516 42	75 011 42	120	413	18	2,5
Alien XL LED 2000 840	2260	1 516 43	75 018 15	120	413	18	2,5
Alien XL LED 2000 830 Sensor	 2180	1 516 44	75 011 43	120	413	18	2,5
Alien XL LED 2000 840 Sensor	 2260	1 516 45	75 018 16	120	413	18	2,5
Alien XL LED 2000 830 Eco	2180	1 516 46	75 011 44	120	413	18	2,5
Alien XL LED 2000 840 Eco	2260	1 516 47	75 018 17	120	413	18	2,5
Alien XL LED 2000 830 Sensor Eco	 2180	1 516 48	75 011 45	120	413	18	2,5
Alien XL LED 2000 840 Sensor Eco	 2260	1 516 57	–	120	413	18	2,7
Alien XL LED 2000 830 Dalisensor Eco	 2180	1 516 49	75 018 18	120	413	18	2,5
Alien XL LED 2000 840 Dalisensor Eco	 2260	1 516 59	–	120	413	18	2,7
Alien XL LED 2000 830 Nöd	2180	1 516 50	75 011 46	120	413	18	2,7
Alien XL LED 2000 840 Nöd	2260	1 516 51	75 018 19	120	413	18	2,7
Alien XL LED 2000 830 Nöd Sensor	 2180	1 516 52	75 011 47	120	413	18	2,7
Alien XL LED 2000 840 Nöd Sensor	 2260	1 516 53	75 018 20	120	413	18	2,7
Alien XL LED 2000 830 Nöd Sensor Eco	 2180	1 516 54	75 011 48	120	413	18	2,7
Alien XL LED 2000 840 Nöd Sensor Eco	 2260	1 516 55	75 018 21	120	413	18	2,7