



Wiresuspension with friction lock

Suspended luminaire with up and down lights for use in offices.

Sheetmetal housing with RAL 9010 textured white paint.

Silver-grey anti-glare louvre with diffuserplate.

Supplied with a halogen-free cable (2.2 m), earthed plug and a wiresuspension with a friction lock. Two pull-switches for separate activation of up and down lights. Dustprotector as standard.

Sensor

Integrated sensor that activates the light after detecting movement.

TD

Light control with two pull-microswitches.

Sensor TD

Light control with two pull-microswitches and an integrated sensor that activates the light after detecting movement.

Actilume

Philips Actilume system with integrated sensor and light control according to daylight level.



AirC:

Sensorsystems with daylightcontrol that can be programmed via app. The sensor can also communicate wirelessly with more sensors. Wireless switches can be integrated in this system.

Lifespan: L80 Ta25 70000h (B50)
MacAdam 3 SDCM CRI >80



Accessories	Art no.	E no.
Rail for T-profile 600	9 551 90	79 551 90
Hook for T-profile	9 551 92	79 551 92
Switches AirC SwitchDim 1 polig	9 688 20	79 852 54



Type	Lumen	Art no.	E no.	L	W	H	c/c	Power	Weight
FlatLED 12.2 830	6130	1 571 01	70 115 57	1274	168	39	1200	50	5
FlatLED 12.2 830 TD *	6130	1 571 05	70 115 58	1274	168	39	1200	50	5
FlatLED 12.2 830 Sensor	6130	1 571 13	70 115 59	1274	168	39	1200	50	5
FlatLED 12.2 830 Sensor TD *	6130	1 571 17	70 115 60	1274	168	39	1200	50	5
FlatLED 12.2 830 Actilume *	6130	1 571 09	70 115 63	1274	168	39	1200	50	5
FlatLED 12.2 830 AirC *	6130	1 571 21	70 180 42	1274	168	39	1200	50	5
FlatLED 12.2 840	6380	1 571 03	70 116 57	1274	168	39	1200	50	5
FlatLED 12.2 840 TD *	6380	1 571 07	70 116 58	1274	168	39	1200	50	5
FlatLED 12.2 840 Sensor	6380	1 571 15	70 116 60	1274	168	39	1200	50	5
FlatLED 12.2 840 Sensor TD *	6380	1 571 19	70 116 66	1274	168	39	1200	50	5
FlatLED 12.2 840 Actilume *	6380	1 571 11	70 116 67	1274	168	39	1200	50	5
FlatLED 12.2 840 AirC *	6380	1 571 23	70 180 43	1274	168	39	1200	50	5