



Industrial fixture for damp and aggressive environments, laundry rooms, etc.

Enclosed IP65 luminaire which meets D-marking requirements. Stainless steel (AISI 304) housing and tempered glass. C4 corrosion classification.

Connection via ends. 3-phase 5x2.5mm<sup>2</sup> throughwiring, with dimming as standard single-phase throughwiring.



Fitted flush to ceiling, on adjustable bracket, rails or wires.

Equipped with robust industrial driver with high resilience against power surges.

Dimmable version (TDC) with push-button, Dali and integrated corridor function.

Lifespan L80 Ta25 80000h (B50)  
MacAdam 3 SDCM CRI: >80

IP 65 | IK 08 | CE



Type	Lumen	Art no.	E no.	L	W	H	c/c	Power	Weight
Inox LED 5000 830	4990	6 602 60	72 135 46	1605	135	95	1395	44	6
Inox LED 5000 840	5200	6 602 62	72 135 47	1605	135	95	1395	44	6
Inox LED 5000 830 TDC *	4990	6 602 64	72 135 48	1605	135	95	1395	44	6
Inox LED 5000 840 TDC *	5200	6 602 66	72 135 49	1605	135	95	1395	44	6
Inox LED 7000 830	6560	6 602 70	72 158 60	1605	135	95	1395	61	6
Inox LED 7000 840	6830	6 602 72	72 158 61	1605	135	95	1395	61	6
Inox LED 7000 830 TDC *	6560	6 602 74	72 158 62	1605	135	95	1395	61	6
Inox LED 7000 840 TDC *	6830	6 602 76	72 158 63	1605	135	95	1395	61	6

\* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.