DOWNLIGHT | NEMO 3 LED





Rails for soft

ceilings



Plate for soft ceilings

Accessories	Art no.	E no.	
Rails for soft ceilings	9 687 01	74 677 01	
Plate for soft ceilings	9 665 45	75 011 49	

Туре	Lumen	Art no.	E no.	Power	Weight
Nemo 3 LED 1100 830	1190	2 813 01	74 643 00	10	0,6
Nemo 3 LED 1100 840	1240	2 813 03	74 643 01	10	0,6
Nemo 3 LED 1100 830 TD *	1190	2 813 21	74 643 02	10	0,6
Nemo 3 LED 1100 840 TD *	1240	2 813 23	74 643 03	10	0,6

* Equipped with Dali dimming driver or push-button.



Downlight for recessed mounting.

Rim of diecasted aluminium, as standard white RAL 9016.

Other parts made from Aluzink, anodised aluminium cooling.

Faceted high-gloss pure aluminium reflector.

20-degree beamangle.

Mounted to ceiling with spring clasps. Separate component unit as standard.

As standard with Halogen-free 2.5 m cable with earthed plug Dimmable version (TD) also equipped with separate 2-wires for control.

Lifespan L80 Ta25 50000h (B50) MacAdam 3 SDCM CRI: >80

IP 21 | CE





