NOKALUX





Rails for soft ceilings



Accessories	Art no.	E no.
Rails for soft ceilings	9 687 01	74 677 01
Plate for soft ceilings	9 665 45	75 011 49

Туре	Lumen	Art no.	E no.	Power	Weight
Nemo 4 LED 1100 830	930	2 814 01	74 684 93	10	0,7
Nemo 4 LED 1100 840	950	2 814 03	74 642 98	10	0,7
Nemo 4 LED 1100 830 TD *	930	2 814 21	74 684 94	10	0,7
Nemo 4 LED 1100 840 TD *	950	2 814 23	74 642 99	10	0,7

^{*} Equipped with Dali dimming driver or push-button.

DOWNLIGHT | NEMO 4 LED

Downlight for recessed mounting.

Rim of diecasted aluminium, as standard white RAL 9016.

Other parts made from Aluzink, anodised aluminium cooling.

Faceted high-gloss pure aluminium reflector.

20-degree beamangle.

Mounted to ceiling with spring clasps. Separate component unit as standard.

As standard with Halogen-free 2.5 m cable with earthed plug Dimmable version (TD) also equipped with separate 2-wires for control.

Lifespan L80 Ta25 50000h (B50) MacAdam 3 SDCM CRI: >80

IP 44 | CE





