



Downlight for recessed fitting.

Rim of diecasted aluminium, as standard white RAL 9016.

Other parts made from Aluzink, anodised aluminium cooling

Faceted high-gloss pure aluminium reflector.

70-degree beam angle.

Mounted to ceiling with spring clasps. Separate component unit as standard.

Comes as standard with Halogen-free 2.5 m cable with earthed plug
Dimmable version (TD) also equipped with separate 2-wires for control.

Lifespan L80 Ta25 50000h (B50)
MacAdam 3 SDCM CRI: >80

IP 21 | CE





Rails for soft ceilings



Plate for soft ceilings

Accessories	Art no.	E no.
Rails for soft ceilings	9 687 01	74 677 01
Plate for soft ceilings	9 665 42	75 062 58



Type	Lumen	Art no.	E no.	Power	Weight
Nemo 6 LED 1100 830	1330	2 816 01	74 642 87	10	1,3
Nemo 6 LED 1100 840	1380	2 816 03	74 642 88	10	1,3
Nemo 6 LED 2000 830	2020	2 816 13	74 642 93	15	1,3
Nemo 6 LED 2000 840	2110	2 816 15	74 642 95	15	1,3
Nemo 6 LED 1100 830 TD *	1330	2 816 21	74 642 89	10	1,3
Nemo 6 LED 1100 840 TD *	1380	2 816 23	74 642 91	10	1,3
Nemo 6 LED 2000 830 TD *	2020	2 816 25	74 642 96	15	1,3
Nemo 6 LED 2000 840 TD *	2110	2 816 27	74 642 97	15	1,3

* Equipped with Dali dimming driver or push-button.