



Rotatable and adjustable downlight for recessed mounting

Diecasted aluminium frame, as standard white RAL 9016 or black RAL 9005. Frosted black polycarbonate anti-glare rings.

Cast aluminium cooling body.

Faceted high-gloss pure aluminium reflector. 45 degree beam angle

Rotatable 360 degrees and 35 degree tiltable.

Mounted in suspended ceiling with spring clasps. Separate component unit as standard.

Comes as standard with Halogen-free 2.5 m cable with earthed plug. Dimmable version (TD) also equipped with separate 2-wires for control.

Lifetime L80 Ta25 50000h (B50)  
MacAdams 3 SDCM CRI: >80

IP 20 | CE





Rails for soft ceilings



Plate for soft ceilings

Accessory	Art.no.	E-no.
Rails for soft ceilings	9 687 01	74 677 01
Plate for soft ceilings	9 665 45	75 011 49



Type	Lumen	Art.no. White	E-no.	Lumen	Art.no. Black	E-no.	Power	Weight
Neptun 2000 830	1980	2 818 01	74 021 67	1980	2 818 31	74 743 22	19	1,6
Neptun 2000 840	2020	2 818 03	74 021 68	2020	2 818 33	74 743 23	19	1,6
Neptun 4000 830	3840	2 818 05	74 021 69	3840	2 818 35	74 743 24	42	1,6
Neptun 4000 840	3920	2 818 07	74 021 70	3920	2 818 37	74 743 25	42	1,6
Neptun 2000 830 TD *	1980	2 818 09	74 021 71	1980	2 818 39	74 743 26	19	1,6
Neptun 2000 840 TD *	2020	2 818 11	74 021 72	2020	2 818 41	74 743 27	19	1,6
Neptun 4000 830 TD *	3840	2 818 13	74 021 73	3840	2 818 43	74 743 28	42	1,6
Neptun 4000 840 TD *	3920	2 818 15	74 021 74	3920	2 818 45	74 743 29	42	1,6

\* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.