



Wall or ceiling plafoniere.

White housing and opal polycarbonate diffuser. Bayonetfixing for the diffuser. High-impact luminaire that meets IK 10 requirements.

Available with sensor or dimmable versions and also with 60 min emergency lighting operation.

Eco for SwitchDim, Dali or DSI dimming and Corridor function.



Sensor turns on and off with motion.





Sensor Eco lights with 10% lightlevel, increases to 100% when presence is detected.

ECO Dalisensor has several possible settings depending on requirements.

Lifespan L80 Ta25 50000h (B50)  
MacAdam 3 SDCM CRI: >80

IP 54 | IK 10 | CE  SENSOR



Type	Lumen	Art no.	E no.	H	Ø	Power	Weight
Saturn LED 2000 830	2220	1 565 42	75 011 35	135	430	18	2,5
Saturn LED 2000 830 Sensor 	2220	1 565 44	75 011 36	135	430	18	2,5
Saturn LED 2000 830 Eco	2220	1 565 46	75 011 37	135	430	18	2,5
Saturn LED 2000 830 Sensor Eco 	2220	1 565 48	75 011 38	135	430	18	2,5
Saturn LED 2000 830 Emergency	2220	1 565 50	75 011 39	135	430	18	2,7
Saturn LED 2000 830 Emergency Sensor 	2220	1 565 52	75 011 40	135	430	18	2,7
Saturn LED 2000 830 Emergency Sensor Eco 	2220	1 565 54	75 011 41	135	430	18	2,7